

CAT. No. **80101** EUROPEAN CEE 7/7 SCHUKO 16 AMPERE 250 VOLT DETACHABLE POWER CORD, (EU1-16P) DIN 49441 PLUG, IEC 60320 C-19 STRAIGHT CONNECTOR, 2 POLE-3 WIRE GROUNDING, 2.5 METERS (8FT.-2IN.) LONG. BLACK.

APPROVALS	VDE <input checked="" type="checkbox"/>	DEMKO <input checked="" type="checkbox"/>	FI <input checked="" type="checkbox"/>	IMQ <input checked="" type="checkbox"/>	NEMKO <input checked="" type="checkbox"/>	SEMKO <input checked="" type="checkbox"/>	SEV <input checked="" type="checkbox"/>
CERTIFICATIONS	REACH <input checked="" type="checkbox"/>	ROHS <input checked="" type="checkbox"/>	CE <input checked="" type="checkbox"/>				
STANDARDS	CEE 7/7 <input checked="" type="checkbox"/>	IEC 60320 C-19 <input checked="" type="checkbox"/>	DIN 49441 <input checked="" type="checkbox"/>				

RELATED POWER CORDS

<u>CATALOG No</u>	<u>LENGTH</u>
80101	2.5 METERS
80101-RA	2.5 METERS
80101-LA	2.5 METERS
80101x6FT	1.8 METERS
80101x10FT	3 METERS
80101x12FT	3.66 METERS
80101x15FT	4.6 METERS

SPECIFICATIONS:

1. OVERALL LENGTH: 2.5 METERS (8FT.-2IN.)
2. CONDUCTORS: 1.5 MM² x 3 (BROWN/BLUE/GREEN-YELLOW)
3. JACKET: H05VV-F, BLACK
4. PLUG: CEE 7/7 "SCHUKO" BLACK, DIN 49441
5. CONNECTOR: IEC 60320 C-19, STRAIGHT, BLACK
6. RATED: 16 AMPERE 250 VOLT
7. TEMPERATURE RATING: 70°C
8. CABLE DIAMETER (APPROX.): 7.0 mm
9. GENERAL MATERIAL: PVC
10. STRANDING (APPROX.): 32/0.2 mm
11. OPERATING TEMPERATURE: -15°C TO +70°C

