

CAT. No.

81580X5M

EUROPEAN CEE 7/7 SCHUKO 16 AMPERE 230-250 VOLT POWER SUPPLY CORD, (EU1-16P) DIN 49441 ANGLED PLUG, STRIPPED ENDS, 2 POLE-3 WIRE GROUNDING, 5 METERS (16FT.-5IN.) LONG. BLACK.

APPROVALS	CEBEC <input checked="" type="checkbox"/>	KEMA <input checked="" type="checkbox"/>	NEMKO <input checked="" type="checkbox"/>	OVE <input checked="" type="checkbox"/>	SEMKO <input checked="" type="checkbox"/>	UTE <input checked="" type="checkbox"/>	VDE <input checked="" type="checkbox"/>
CERTIFICATIONS	REACH <input checked="" type="checkbox"/>	ROHS <input checked="" type="checkbox"/>	CE <input checked="" type="checkbox"/>				
STANDARDS	CEE 7/7 <input checked="" type="checkbox"/>	DIN 49441 <input checked="" type="checkbox"/>					

RELATED POWER CORDS

<u>CATALOG No</u>	<u>LENGTH</u>
81580	2.5 METERS
81580X10FT	10 FEET
81580X2M	2 METERS
81580X3M	3 METERS
81580X4.5M	4.5 METERS
81580X5M	5 METERS

SPECIFICATIONS:

1. OVERALL LENGTH: 5 METERS (16FT.-5IN.)
2. CONDUCTORS: 1.5 MM² x 3 (BROWN/BLUE/GREEN-YELLOW)
3. JACKET: H05VV-F, BLACK
4. PLUG: CEE 7/7 ANGLED "SCHUKO" BLACK, DIN 49441
5. CONNECTOR: NONE
6. RATED: 16 AMPERE 250 VOLT
7. TEMPERATURE RATING: 70°C
8. CABLE DIAMETER (APPROX.): 8.0 mm
9. GENERAL MATERIAL: PVC
10. STRANDING (APPROX.): 32/0.2 mm
11. OPERATING TEMPERATURE: -15°C TO +70°C

