



**CAT. 57090-M**

IEC 60320 C-19 CONNECTOR, 2 POLE 3 WIRE, 20A-250V, UL/CSA LISTED. (ACCEPTS 14/3 - 10/3 AWG COND.), CORD GRIP RANGE WITH DUST SHIELD = .360-.655. BLACK.




**CAT. 57090-V**

IEC 60320 C-19 CONNECTOR, 2 POLE 3 WIRE, 20A-250V, UL/CSA, LISTED. (ACCEPTS 14/3-12/3 AWG COND.), CORD GRIP RANGE = .360-.472, BLACK.




**CAT. 57090-RA (RIGHT ANGLE) CE MARK**

IEC 60320 C-19 RIGHT ANGLE CONNECTOR, 2 POLE 3 WIRE, 20A-125V, 20A-250V(UL/CSA), 16A-250V (VDE) (ACCEPTS 14/3 AWG.) CORD GRIP MAX. O.D. - .500 BLACK.




**CAT. 57091 (DOWN ANGLE) CE MARK**

IEC 60320 C-19 DOWN ANGLE CONNECTOR, BLACK RUBBER, 2 POLE 3 WIRE, 16A-250V, VDE APPROVED. ACCEPTS 14/3 AWG COND., CORD GRIP MAX. O.D.=.354  
CAT. 57092 STRAIGHT RUBBER CONNECTOR.



**CAT. 57110-V**

IEC 60320 C-20 PLUG, 2 POLE 3 WIRE, 20A-250V, UL/CSA LISTED. ACCEPTS 14/3 - 12/3 AWG COND., CORD GRIP RANGE = .360 - .472. BLACK.



**CAT. 57110-RA (RIGHT ANGLE) CE MARK**

IEC 60320 C-20 RIGHT ANGLE PLUG, 2 POLE 3 WIRE, 20A-125V, 20A-250V(UL/CSA), 16A-250V (VDE) (ACCEPTS 14/3 AWG.) CORD GRIP MAX. O.D. = .500. BLACK.