

CAT. No.
57060-NS

IEC 60320 (320) C-13,C-15 CONNECTOR, RIGHT ANGLE CORD GRIP, BLACK, BOX TYPE TERMINALS ACCEPT 14 AWG (2.5 mm) CONDUCTORS, 2 POLE 3 WIRE GROUNDING
STANDARD:IEC60320 (320)

15 AMP 250 VOLT

APPROVALS / CERT'S.

CSA

UL

10AMP 250 VOLT

APPROVALS / CERT'S.


VDE

ALL DIMENSIONS ARE IN MILLIMETERS

MAXIMUM JACKET O.D. ACCEPTED BY EXTERNAL STRAIN RELIEF = 7 DIA (0.276")
MAXIMUM JACKET O.D. ACCEPTED BY INTERNAL STRAIN RELIEF = 10 DIA (0.394")
MAXIMUM CONDUCTOR SIZE ACCEPTED BY TERMINALS = 2.5 (14 AWG)

CORDAGE PREPARATION

CONDUCTOR INSULATION COLOR	CONDUCTOR COLOR CODE	"LENGTH"	"STRIP"
GREEN / YELLOW	GROUND	33	6
BLUE	NEUTRAL	22	6
BROWN	LINE	50	6



CORDAGE PREPARATION

