

CAT. No.  
**62250**

IEC320C-13,4 OUTLET POWER STRIP, ILLUMINATED 10 AMP DOUBLE POLE CIRCUIT BREAKER, IEC 320 C-14  
INLET, SURGE PROTECTED, FILTER, SURFACE MOUNT, 2 POLE 3 WIRE, 10 AMP 250 VOLT

CERTIFICATION CE

### ALL DIMENSIONS ARE IN MILLIMETERS

#### R.F. FILTER TECHNICAL SPECIFICATION

LINE FREQUENCY	0 TO 400 Hz
OPERATING VOLTAGE	115 TO 250 VOLTS a.c.
RATED CURRENT	10 AMPS
INSULATION RESISTANCE	6000M (100 VOLTS d.c.)
LEAKAGE CURRENT	2x0.21mA (250 Volts 50 Hz)
TYPICAL ATTENUATION	75dB (100kHz TO 100MHz)
EARTH CHOKE	0.4mH
CLIMATIC CATEGORY	IEC68 25/85/21 DIN 40040
TEMPERATURE RANGE	-25°C TO +85°C

THE FILTERS ARE FITTED WITH ZNR VOLTAGE TRANSIENTS

STANDARD SPEC. Z280G	
MAX. CONT. VOLTS AC RMS @ 25°C	320
MAX CONT. VOLTS DC @ 25°C	416
VARISTOR V MIN @ 1mA	450
ENERGY JOULES 10/1000	140
CLAMPING VOLT @ 100 AMPS	825
m WATTS CONT.	800

