

CAT. No.

74456x45

GFCI (RCD) MODULE, SINGLE POLE CIRCUIT BREAKER, 10 AMPERE 230 VOLT, 50/60 Hz, 10mA TRIP LEVEL, 45 X 45mm SNAP-IN, MOUNTING SIZE, WHITE, CE MARK

CERTIFICATIONS

CE

ALL DIMENSIONS ARE IN MILLIMETERS

NOTE:

1. DOWNSTREAM OUTLETS CAN ALSO BE PROTECTED.
2. NO RESET REQUIRED AFTER POWER FAILURE (LATCHED RCD)
3. OPERATIONAL TEMPERATURE  $-5^{\circ}\text{C}$  TO  $+40^{\circ}\text{C}$
4. TERMINAL TORQUE = 0.08 Nm NEWTON METERS
5. NOTE: CANNOT BE USED ON 125 VOLT (PHASE TO NEUTRAL) OR 250 VOLT (125V / 125V PHASE TO PHASE) U.S. TYPE ELECTRICAL CIRCUITS
6. NOT SUITABLE FOR APPLIANCES THAT HAVE INTERNAL FILTER CONDENSERS WITH CONNECTIONS BETWEEN PHASE/NEUTRAL, PHASE/GROUND, NEUTRAL/GROUND

