

CAT. No. <b>85113-C15</b>	THAILAND 10 AMPERE 250 VOLT POWER CORD, TYPE O (TH1-16P), (TIS 166-2549) PLUG, H05VV-F 1.0mm <sup>2</sup> CORDAGE, IEC 60320 C-15 CONNECTOR, 2 POLE-3 WIRE GROUNDING (2P+E), 2.5 METERS (8FT-2IN) (98") LONG. BLACK.
------------------------------	--


APPROVALS	TISI <input checked="" type="checkbox"/>
CERTIFICATIONS	REACH <input checked="" type="checkbox"/> ROHS <input checked="" type="checkbox"/> ROHS2 <input checked="" type="checkbox"/> ROHS3 <input checked="" type="checkbox"/> CE <input checked="" type="checkbox"/>
STANDARDS	TIS 166-2549 <input checked="" type="checkbox"/> IEC 60320 C-15 <input checked="" type="checkbox"/>

**SPECIFICATIONS:**

1. OVERALL LENGTH: 2.5 METERS (8FT-2IN)
2. CONDUCTORS: 1.0mm<sup>2</sup> x 3 (BROWN/BLUE/GREEN-YELLOW)
3. JACKET: H05VV-F, BLACK
4. PLUG: TIS 166-2549, STRAIGHT, BLACK
5. CONNECTOR: IEC 60320 C-15, STRAIGHT, BLACK
6. RATED: 10 AMPERE 250 VOLT
7. TEMP. RATING: 70°C

**RELATED POWER CORDS:**

CATALOG No	DESCRIPTION
85113	THAILAND TO C-13, 2.5 METERS
85113X10FT	THAILAND TO C-13, 10 FEET
85113-RA	THAILAND TO RIGHT ANGLE C-13, 2.5 METERS
85113-LA	THAILAND TO LEFT ANGLE C-13, 2.5 METERS
85113-LK	THAILAND TO LOCKING C-13, 2.5 METERS
85105	THAILAND TO C-5, 1.8 METERS
85113-C15	THAILAND TO C-15, 2.5 METERS
85119	THAILAND TO C-19, 2.5 METERS
85119-LK	THAILAND TO LOCKING C-19, 2.5 METERS
85130	THAILAND TO STRIPPED ENDS, 10A-250V, 8 FEET
85130X10FT	THAILAND TO STRIPPED ENDS, 10A-250V, 10 FEET
85140	THAILAND TO STRIPPED ENDS, 16A-250V, 8 FEET
85245-BLK	THAILAND PLUG, BLACK
85160-BLK	THAILAND CONNECTOR, BLACK
85164	THAILAND POWER CORD



**TH1-16P.**  
**TIS 166-2549**

**C-15 CONNECTOR**