

CAT. No.

90521X9FT

JUMPER CORD, IEC 60320 C-20 PLUG AND IEC 60320 C-19 CONNECTOR, 20 AMPERE-250 VOLT, SJTO, 12/3 AWG CONDUCTORS, 105°C CORDAGE, 2 POLE-3 WIRE GROUNDING, 2.74 METERS (9 FT.) LONG. BLACK.

APPROVALS	UL <input checked="" type="checkbox"/> C-UL <input checked="" type="checkbox"/>
CERTIFICATIONS	REACH <input checked="" type="checkbox"/> ROHS <input checked="" type="checkbox"/>
STANDARDS	IEC 60320 <input checked="" type="checkbox"/>

RELATED POWER CORDS

<u>CATALOG No</u>	<u>LENGTH</u>
90521	2.5 METERS
90521X2FT	2 FEET
90521X3FT	3 FEET
90521X4FT	4 FEET
90521X5FT	5 FEET
90521X6FT	6 FEET
90521X7FT	7 FEET
90521X8FT	8 FEET
90521X9FT	9 FEET
90521X10FT	10 FEET
90521X12FT	12 FEET
90521X15FT	15 FEET
90521X5M	5 METERS

SPECIFICATIONS:

- | | |
|------------------------------|----------------------------------|
| 1. OVERALL LENGTH: | 2.74 METERS (9 FT.) |
| 2. CONDUCTORS: | 12 AWG x 3 (BLACK, WHITE, GREEN) |
| 3. JACKET: | SJTO, 105°C, BLACK |
| 4. PLUG: | IEC 60320 C-20, STRAIGHT, BLACK |
| 5. CONNECTOR: | IEC 60320 C-19, STRAIGHT, BLACK |
| 6. RATED: | 20 AMPERE 250 VOLT |
| 7. CABLE DIAMETER (APPROX.): | 11 mm |
| 8. GENERAL MATERIAL | PVC |
| 9. STRANDING (APPROX.): | 65/0.254 mm |

