

CAT. No.

98216X36IN

UNIVERSAL DETACHABLE CORD SET, IEC 60320 C-14 PLUG AND IEC 60320 C-13 CONNECTOR, 10 AMPERE 250 VOLT, SJTO, 105°C CORDAGE, 2 POLE-3 WIRE GROUNDING, 0.9 METERS (36 INCHES) LONG, BLACK.

| | |
|----------------|---|
| APPROVALS | UL <input checked="" type="checkbox"/> CSA <input checked="" type="checkbox"/> VDE <input checked="" type="checkbox"/> DEMKO <input checked="" type="checkbox"/> FI <input checked="" type="checkbox"/> IMQ <input checked="" type="checkbox"/> NEMKO <input checked="" type="checkbox"/> SEMKO <input checked="" type="checkbox"/> SEV <input checked="" type="checkbox"/> |
| CERTIFICATIONS | REACH <input checked="" type="checkbox"/> ROHS <input checked="" type="checkbox"/> CE <input checked="" type="checkbox"/> |
| STANDARDS | IEC 60320 <input checked="" type="checkbox"/> |

RELATED POWER CORDS:

| CATALOG No | LENGTH |
|------------|------------|
| 98226 | 2.5 METERS |
| 98220 | 2 METERS |
| 98230 | 3 METERS |
| 98230X5M | 5 METERS |
| 98216 | 1 METER |
| 98216X12IN | 12 INCHES |
| 98216X18IN | 18 INCHES |
| 98216X24IN | 24 INCHES |
| 98216X30IN | 30 INCHES |
| 98216X36IN | 36 INCHES |
| 98216X48IN | 48 INCHES |
| 98216X60IN | 60 INCHES |
| 98216X72IN | 72 INCHES |
| 98216X96IN | 96 INCHES |
| 98216X10FT | 10 FEET |
| 98216X12FT | 12 FEET |
| 98216X15FT | 15 FEET |
| 98216X20FT | 20 FEET |
| 98226-Y | 2.5 METERS |
| 98226-Y18 | 18 INCHES |
| 98226-Y72 | 72 INCHES |

SPECIFICATIONS:

- OVERALL LENGTH: 0.9 METERS (36 INCHES)
- CONDUCTORS: 1.0 mm² x 3 (17 AWG X 3)
- JACKET: H05VV (SJTO), 105°C, BLACK
- PLUG: IEC 60320 C-14, STRAIGHT, BLACK
- CONNECTOR: IEC 60320 C-13, STRAIGHT, BLACK
- RATED: 10 AMPERE 250 VOLT
- CABLE DIAMETER (APPROX.): 8.0 mm
- GENERAL MATERIAL: PVC

