


SWISS CORD SETS & POWER CORDS

10 Ampere 250 Volt, 2 Pole 3 Wire Grounding	SW1-10P		10 A / 250 V
16 Ampere 250 Volt, 2 Pole 3 Wire Grounding	SW2-16P		16 A / 250 V
2.5 Ampere 250 Volt, 2 Pole 2 Wire	Europlug		2.5 A / 250 V

General Specification Data

Conductor Color Code:	Brown, Blue, Green/Yellow (3 wire); Brown, Blue (2 wire)
Plug Standards:	SEV 1011, CEE 7/16 (Non-Polarized)
Conductor Size / Rating:	0.75 mm ² @6 Ampere, 1.0 mm ² @ 10 Ampere, 1.5 mm ² @ 16 Ampere
Jacket O.D. (Approx.):	6.4 mm = 3 x 0.75 mm ² , 7.2 mm = 3 x 1.0 mm ² , 8.3 mm = 3 x 1.5 mm ²
Material:	PVC, Jacket Color Black, Temperature 70°C.
Connector Standards:	IEC 60320 (320) C-13, C-19, C-5, C-7, C-15
Cordage Standards:	H05VV-F3G, H03VV-F3, H03VV-H2, H05VV-H2, H05VV-F2, CENELEC HD-21 (HAR)
Cord Set Length:	2.5 meters/8'-2", 1.8 meters/6'



Power Cord - Detachable Cord Sets

Catalog #	Rating	Description	Length	Approvals
85101	10 A 250 V	Straight C-13 connector	2.5 m	18
85101-LA	10 A 250 V	Left angle C-13 connector	2.5 m	18
85101-RA	10 A 250 V	Right angle C-13 connector	2.5 m	18
		Cordage - H05VV-F3G 1.0 mm ²		
85150	16 A 250 V	Straight C-19 connector	2.5 m	18
		Cordage - H05VV-F3G 1.5 mm ²		
85950	2.5 A 250 V	Straight C-5 connector	1.8 m	18
		Cordage - H03VV-F3 0.75 mm ²		
81900	2.5 A 250 V	Straight C-7 connector	1.8 m	18 and (A)
		Cordage - H03VV-H2 0.75 mm ²		

SW1-10P	"CE" MARK	IEC 60320 C-13
SW2-16P		IEC 60320 C-19
SW1-10P		IEC 60320 C-5
Europlug	"CE" MARK	IEC 60320 C-7
(A) 2, 4, 7, 9, 12, 13, 14, 17, 21, 22		

Power Supply Cords

Catalog #	Rating	Description	Conductors	Length	Approvals
85010	6 A 250 V	Straight plug	0.75 mm ²	2.5 m	18
85040	10 A 250 V	Straight plug	1.0 mm ²	2.5 m	18
		Cordage - H05VV-F3G			
85050	16 A 250 V	Straight plug	1.5 mm ²	2.5 m	18
		Cordage - H05VV-F3G			
90400	2.5 A 250 V	6.4 mm diameter cord		1.8 m	18 and (A)
		Cordage - H05VV-F2 0.75 mm ²			
90200	2.5 A 250 V	3.4 x 5.6 oval cord		1.8 m	18 and (A)
		Cordage - H03VV-H2F2 0.75 mm ²			

SW1-10P	
SW2-16P	
Europlug	
(A) 2, 4, 7, 12, 13, 14, 17, 21, 22	

- Black standard color. White and gray available.
- Custom lengths and shielded cords available.
- Various terminals, custom stripping, hanked cords available.
- IEC 60320 C-15 120°C type connector available on some models.

Approvals: 1.ASTA 2.CEBC 3.CSA 4.DEMKO 5.PSE 6.DFT 7.FI 8.GS 9.IMQ 10.JET 11.JIS 12.KEMA 13.NEMKO 14.OVE 15.SAA 16.SABS 17.SEMKO 18.SEV 19.SII 20.UL, C-UL 21.UTE 22.VDE 23.ISO 24.CCC 25.IRAM 26.BSI

