


NORTH AMERICAN CORD SETS

20 Ampere 125 Volt, 2 Pole 3 Wire Grounding NEMA L5-20P  20 A / 125 V

20 Ampere 250 Volt, 2 Pole 3 Wire Grounding NEMA L6-20P  20 A / 250 V

General Specification Data

Conductor Color Code: North American (N.A.) Black (Line), White (Neutral), Green (Ground)
International (Int'l.) Brown (Line), Blue (Neutral), Green/Yellow (Ground)
Plug Standards: UL 498, CSA, NEMA, ANSI
Conductor Size / Rating: 14 AWG @ 15 Ampere, 12 AWG @ 20 Ampere
Jacket O.D. (Approx.): 14 AWG = .370", 12 AWG = .445"
Material: PVC, Jacket Color Black, Temperature 105°C
Connector Standards: IEC 60320 (320) C-13, C-19
Cordage Standards: SJTO
Cord Set Length: 2.5 meters/8'-2"



Power Cord - Detachable Cord Sets

Catalog #	Rating	Plug / Connect.	Cond's.	Length	App'ls	
92900	15 A 125 V	L5-20P / C-13	14/3 AWG	2.5 m	3, 20	NEMA L5-20P  IEC 60320 C-13 
90900	20 A 125 V	L5-20P / C-19	12/3 AWG	2.5 m	3, 20	NEMA L5-20P  IEC 60320 C-19 
93900	15 A 250 V	L6-20P / C-13	14/3 AWG	2.5 m	3, 20	NEMA L6-20P  IEC 60320 C-13 
90950	20 A 250 V	L6-20P / C-19	12/3 AWG	2.5 m	3, 20	NEMA L6-20P  IEC 60320 C-19 
90950x5M	20 A 250 V	L6-20P / C-19	12/3 AWG	5.0 m	3, 20	
90950x5MRA	20 A 250 V	L6-20P / Right Angle C-19	12/3 AWG	5.0 m	3, 20	

- Black standard color.
- Various terminals, custom stripping, hanked cords available.
- 10, 12, 16 foot lengths available. Minimum order may apply.

Approvals: 1.ASTA 2.CEBC 3.CSA 4.DEMKO 5.PSE 6.DFT 7.FI 8.GS 9.IMQ 10.JET 11.JIS 12.KEMA 13.NEMKO
14.OVE 15.SAA 16.SABS 17.SEMKO 18.SEV 19.SII 20.UL, C-UL 21.UTE 22.VDE 23.ISO 24.CCC 25.IRAM 26.BSI

