

NORTH AMERICAN POWER CORDS

2 Pole 3 Wire Grounding

20 Ampere 125 VoltNEMA L5-20P



30 Ampere 125 VoltNEMA L5-30P



20 Ampere 250 VoltNEMA L6-20P



30 Ampere 250 VoltNEMA L6-30P



General Specification Data

Conductor Color Code: North American (N.A.) Black (Line), White (Neutral), Green (Ground)
International (Int'l.) Brown (Line), Blue (Neutral), Green/Yellow (Ground)

Plug Standards: UL 498, CSA, NEMA, ANSI

Conductor Size / Rating: 12 AWG @ 20 Ampere, 10 AWG @ 30 Ampere

Jacket O.D. (Approx.): 12 AWG = .445", 10 AWG = .670"

Material: PVC, Jacket Color Black, Temperature 105°C

Cordage Standards: SJTO

Cord Set Length: 2.5 meters/8'-2", 4.6 meters/15'

Power Supply Cords

Catalog #	Rating	Plug Type	Conductors	Length	Approvals	
94920 ⁽¹⁾	20 A 125 V	L5-20P	12/3 AWG	2.5 m	3, 20	
94940 ⁽¹⁾	20 A 250 V	L6-20P	12/3 AWG	2.5 m	3, 20	
94950 ⁽¹⁾	30 A 125 V	L5-30P	10/3 AWG	4.6 m	3, 20	
94960 ⁽¹⁾	30 A 250 V	L6-30P	10/3 AWG	4.6 m	3, 20	

- (1) NEMA L5-20C, L6-20C, L5-30C and L6-30C locking connectors can be provided for extension cord applications.
- 8, 10, 12, 15 foot lengths available. Minimum order may apply.
 - Black standard color.
 - Various terminals, custom stripping, hanked cords available.

Approvals: 1.ASTA 2.CEBEC 3.CSA 4.DEMKO 5.PSE 6.DFT 7.FI 8.GS 9.IMQ 10.JET 11.JIS 12.KEMA 13.NEMKO 14.OVE 15.SAA 16.SABS 17.SEMKO 18.SEV 19.SII 20.UL, C-UL 21.UTE 22.VDE 23.ISO 24.CCC 25.IRAM 26.BSI



International Configurations, Inc. • P.O. Box 3374 • Enfield, Connecticut 06083 • TEL (860) 749-6380 • FAX (860) 749-2985
InternationalConfig.com • Sales@InternationalConfig.com

© 2009 International Configurations, Inc. Entire contents of this catalog copyrighted.