


IEC 60320 C-13 & C-14 ACCESSORY POWER CORDS

13 Ampere / 15 Ampere 250 Volt, 2 Pole 3 Wire Grounding
UL, CSA Listed



IEC 60320 C-13 IEC 60320 C-14

General Specification Data

Conductor Color Code: North American (N.A.) Black (Line), White (Neutral), Green (Ground)
International (Int'l.) Brown (Line), Blue (Neutral), Green/Yellow (Ground)

Plug Standard: IEC 60320 (320) C-14

Conductor Size / Rating: 16 AWG @ 13 Ampere, 14 AWG @ 15 Ampere


Jacket O.D. (Approx.): 16/3 AWG = .345", 14/3 AWG = .380"

Material: PVC, Jacket Color Black



Connector Standard: IEC 60320 (320) C-13

Cordage Standard: SJT 105°C




Cord Set Length: 2.5 meters/8'-2", 2.0 meters/6'-7", 1.0 meters/3'-3"



Power Cord - Detachable Cord Sets

Catalog #	Rating	Description	Length	Approvals		
98525	13 A 250 V	C-14 Plug / C-13 connector	2.5 m	3, 20		
98520	13 A 250 V	C-14 Plug / C-13 connector	2.0 m	3, 20		
98515	13 A 250 V	C-14 Plug / C-13 connector	1.0 m	3, 20		
Cordage - SJT 16/3 AWG						
98625	15 A 250 V	C-14 Plug / C-13 connector	2.5 m	3, 20		
98620	15 A 250 V	C-14 Plug / C-13 connector	2.0 m	3, 20		
98615	15 A 250 V	C-14 Plug / C-13 connector	1.0 m	3, 20		
98625x5M	15 A 250 V	C-14 Plug / C-13 connector	5.0 m	3, 20		
98625-Y ⁽¹⁾	15 A 250 V	C-14 Plug / C-13 connectors	2.5 m	3, 20		
Cordage - SJT 14/3 AWG						

Power Supply Cords

Catalog #	Rating	Description	Length	Approvals	
98575	13 A 250 V	Straight C-13 connector	2.5 m	3, 20	IEC 60320 C-13 
98580	13 A 250 V	Straight C-13 connector	2.0 m	3, 20	
98585	13 A 250 V	Straight C-13 connector	1.0 m	3, 20	
Cordage - SJT 16/3 AWG					
98675	15 A 250 V	Straight C-13 connector	2.5 m	3, 20	IEC 60320 C-13 
98680	15 A 250 V	Straight C-13 connector	2.0 m	3, 20	
98685	15 A 250 V	Straight C-13 connector	1.0 m	3, 20	
Cordage - SJT 14/3 AWG					
98545	13 A 250 V	Straight C-14 plug	2.5 m	3, 20	IEC 60320 C-14 
98550	13 A 250 V	Straight C-14 plug	2.0 m	3, 20	
98555	13 A 250 V	Straight C-14 plug	1.0 m	3, 20	
Cordage - SJT 16/3 AWG					
98645	15 A 250 V	Straight C-14 plug	2.5 m	3, 20	IEC 60320 C-14 
98650	15 A 250 V	Straight C-14 plug	2.0 m	3, 20	
98655	15 A 250 V	Straight C-14 plug	1.0 m	3, 20	
Cordage - SJT 14/3 AWG					

(1) See page 32 for details

- Black standard color. White and gray available.
- Custom lengths and shielded cords available.
- Minimum order may apply on some models.
- Various terminals, custom stripping, hanked cords available.
- IEC 60320 C-15 120°C type connector available on some models.

Approvals: 1.ASTA 2.CEBEC 3.CSA 4.DEMKO 5.PSE 6.DFT 7.FI 8.GS 9.IMQ 10.JET 11.JIS 12.KEMA 13.NEMKO
14.OVE 15.SAA 16.SABS 17.SEMKO 18.SEV 19.SII 20.UL, C-UL 21.UTE 22.VDE 23.ISO 24.CCC 25.IRAM 26.BSI



International Configurations, Inc. • P.O. Box 3374 • Enfield, Connecticut 06083 • TEL (860) 749-6380 • FAX (860) 749-2985
InternationalConfig.com • Sales@InternationalConfig.com

© 2009 International Configurations, Inc. Entire contents of this catalog copyrighted.