

IEC 60320 C-13 & C-14 ACCESSORY POWER CORDS

10 Ampere 250 Volt, 2 Pole 3 Wire Grounding


European / International Approvals



IEC 60320 C-13 IEC 60320 C-14

General Specification Data

Conductor Color Code: International (Int'l.) Brown (Line), Blue (Neutral), Green/Yellow (Ground)
Plug Standard: IEC 60320 (320) C-14
Conductor Size / Rating: 1.0 mm² @ 10 Ampere 250 Volt
Jacket O.D. (Approx.): 1.0 mm² = 7.2 mm
Material: PVC, Jacket Color Black
Connector Standard: IEC 60320 (320) C-13
Cordage Standard: H05VV-F3G
Cord Set Length: 3.1 meters/10', 2.5 meters/8'-2", 2.0 meters/6'-7", 1.0 meters/3'-3"



Power Cord - Detachable Cord Sets

Catalog #	Rating	Description	Length	Approvals	IEC 60320 C-14 "CE" MARK IEC 60320 C-13
90025	10 A 250 V	Straight C-13 connector	2.5 m	22 and (A)	 (A) 2, 4, 7, 12, 13, 14, 17, 18, 26
90020	10 A 250 V	Straight C-13 connector	2.0 m	22 and (A)	
90015	10 A 250 V	Straight C-13 connector	1.0 m	22 and (A)	
90030	10 A 250 V	Straight C-13 connector	3.1 m	22 and (A)	
90025-RA	10 A 250 V	Right angle C-13 connector	2.5 m	22	 IEC 60320 C-14 "CE" MARK IEC 60320 C-13
90020-RA	10 A 250 V	Right angle C-13 connector	2.0 m	22	
90015-RA	10 A 250 V	Right angle C-13 connector	1.0 m	22	
90030-RA	10 A 250 V	Right angle C-13 connector	3.1 m	22	
90025-LA	10 A 250 V	Left angle C-13 connector	2.5 m	22	 IEC 60320 C-14 "CE" MARK IEC 60320 C-13
90020-LA	10 A 250 V	Left angle C-13 connector	2.0 m	22	
90015-LA	10 A 250 V	Left angle C-13 connector	1.0 m	22	
90030-LA	10 A 250 V	Left angle C-13 connector	3.1 m	22	

Power Supply Cords

Catalog #	Rating	Description	Length	Approvals	IEC 60320 C-13 "CE" MARK
90175 ⁽¹⁾	10 A 250 V	Straight C-13 connector	2.5 m	22 and (A)	 (A) 2, 4, 7, 12, 13, 14, 17, 18, 26
90180 ⁽¹⁾	10 A 250 V	Straight C-13 connector	2.0 m	22 and (A)	
90185 ⁽¹⁾	10 A 250 V	Straight C-13 connector	1.0 m	22 and (A)	
90190 ⁽¹⁾	10 A 250 V	Straight C-13 connector	3.1 m	22 and (A)	
90075 ⁽¹⁾	10 A 250 V	Straight C-14 plug	2.5 m	22	 IEC 60320 C-14 "CE" MARK
90080 ⁽¹⁾	10 A 250 V	Straight C-14 plug	2.0 m	22	
90085 ⁽¹⁾	10 A 250 V	Straight C-14 plug	1.0 m	22	
90090 ⁽¹⁾	10 A 250 V	Straight C-14 plug	3.1 m	22	

(1) Add suffix "-RA" to catalog number for Right Angle version and suffix "-LA" for Left Angle version.

- Black standard color. White and gray available.
- Various terminals, custom stripping, hanked cords available.
- Custom lengths and shielded cords available.
- IEC 60320 C-15 120°C type connector available on some models.
- Minimum order may apply on some models.

Approvals: 1.ASTA 2.CEBC 3.CSA 4.DEMKO 5.PSE 6.DFT 7.FI 8.GS 9.IMQ 10.JET 11.JIS 12.KEMA 13.NEMKO 14.OVE 15.SAA 16.SABS 17.SEMKO 18.SEV 19.SII 20.UL, C-UL 21.UTE 22.VDE 23.ISO 24.CCC 25.IRAM 26.BSI

