


# STRAIN RELIEF CORD CONNECTORS

## Liquid-Tight (IP 68)



**STANDARD TYPE**

**LOCKING NUT**

THREAD SIZE*	MAJOR DIAMETER mm	PITCH mm
PG 07	12.5	1.27
PG 09	15.2	1.41
PG 11	18.6	1.41
PG 13.5	20.4	1.41
PG 16	22.5	1.41
PG 21	28.3	1.59
PG 29	37.0	1.59
PG 36	47.0	1.59
PG 42	54.0	1.59
PG 48	59.3	1.59

**FLEX TYPE**

\* Steel Conduit Thread 10 per DIN 40430

**NOTE: Last 2 digits of catalog number indicate "PG" thread size as per above table**

CATALOG NUMBER (BLACK)	DIAMETER RANGE	"A" MOUNTING HOLE CLEARANCE	"B" MAXIMUM OVERALL LENGTH	"C" THREAD LENGTH	"D" WRENCHING NUT THICKNESS	"E" WRENCHING FLATS	"F" LOCKNUT THICKNESS	"G" LOCKNUT DIAMETER
<b>METRIC PG THREAD - STANDARD TYPE</b>								
20607	.079-.197	.492	1.259	.315	.203	.591	.197	.827
20507	.118-.255	.492	1.259	.315	.203	.591	.197	.827
20609	.079-.236	.599	1.378	.315	.218	.750	.197	.945
20509	.157-.314	.599	1.378	.315	.218	.750	.197	.945
20611	.157-.275	.733	1.500	.315	.218	.866	.197	1.024
20511	.200-.394	.733	1.500	.315	.218	.866	.197	1.024
20613	.341-.354	.804	1.614	.354	.218	.945	.236	1.142
20513	.236-.472	.804	1.614	.354	.218	.945	.236	1.142
20616	.423-.481	.886	1.732	.394	.234	1.063	.236	1.300
20516	.394-.551	.886	1.732	.394	.234	1.063	.236	1.300
20621	.481-.617	1.115	1.929	.433	.250	1.299	.276	1.535
20521	.545-.709	1.115	1.929	.433	.250	1.299	.276	1.535
20629	.511-.787	1.457	2.165	.433	.297	1.654	.276	1.968
20529	.708-.984	1.457	2.165	.433	.297	1.654	.276	1.968
20636	.787-1.023	1.850	2.519	.512	.315	2.087	.315	2.598
20536	.866-1.259	1.850	2.519	.512	.315	2.087	.315	2.598
20642	.984-1.220	2.126	2.638	.512	.360	2.362	.315	2.874
20542	1.259-1.496	2.126	2.638	.512	.360	2.362	.315	2.874
20648	1.141-1.378	2.335	2.717	.551	.360	2.559	.315	3.071
20548	1.456-1.732	2.335	2.717	.551	.360	2.559	.315	3.071
<b>METRIC PG THREAD - FLEX TYPE</b>								
21707	.079-.197	.492	2.560	.315	.203	.591	.197	.827
20707	.118-.255	.492	2.560	.315	.203	.591	.197	.827
21709	.079-.236	.599	2.970	.315	.218	.750	.197	.945
20709	.157-.314	.599	2.970	.315	.218	.750	.197	.945
21711	.157-.275	.733	3.510	.315	.218	.866	.197	1.024
20711	.200-.394	.733	3.510	.315	.218	.866	.197	1.024
21713	.341-.354	.804	4.020	.354	.218	.945	.236	1.142
20713	.236-.472	.804	4.020	.354	.218	.945	.236	1.142
21716	.423-.481	.886	4.540	.394	.234	1.063	.236	1.300
20716	.394-.551	.886	4.540	.394	.234	1.063	.236	1.300
21721	.481-.617	1.115	5.293	.433	.250	1.299	.276	1.535
20721	.545-.709	1.115	5.293	.433	.250	1.299	.276	1.535

**ALL DIMENSIONS ARE IN INCHES**

